



# 35×K7(WA)

钢丝绳公称直径 Nominal rope diameter		直径误差 Diameter tolerance		钢丝绳近似重量 Approximate unit Wt.		钢丝绳最小破断拉力 Minimum breaking force(Fmin,MBF)	
						公制单位/Metric unit	
		min.	max.			1960 Grade	2160 Grade
mm	inch	mm	mm	kg/100m	lb/ft	kN	kN
10		10.0	10.4	51.0	0.34	91.8	97.9
	7/16	11.1	11.5	61.0	0.41	111.1	118.2
12		12.0	12.5	73.5	0.49	132.2	141.0
	1/2	12.7	13.2	81.9	0.55	148.0	157.8
13		13.0	13.5	86.2	0.58	155.1	165.5
14		14.0	14.6	100.0	0.67	179.9	192.0
	9/16	14.3	14.9	104.2	0.70	187.6	200.0
15		15.0	15.6	115.0	0.77	206.5	220.4
	5/8	15.9	16.5	131.0	0.88	234.7	250.7
16		16.0	16.6	131.0	0.88	235.0	250.7
18		18.0	18.7	165.0	1.11	297.4	317.3
19		19.0	19.8	184.0	1.24	331.0	353.2
	3/4	19.1	19.9	184.5	1.24	330.7	353.0
20		20.0	20.8	204.0	1.37	366.8	391.4
22		22.0	22.9	247.0	1.66	443.8	473.6
	7/8	22.2	23.1	251.5	1.69	451.6	481.9
24		24.0	25.0	294.0	1.98	528.2	563.6
25		25.0	26.0	319.0	2.14	573.1	611.5
	1	25.4	26.4	328.9	2.21	591.2	630.8
26		26.0	27.0	345.0	2.32	619.9	661.4
27		27.0	28.1	372.0	2.50	668.5	713.3
28		28.0	29.1	400.0	2.69	718.9	767.1
	1-1/8	28.6	29.7	416.7	2.80	748.6	798.8
29		29.0	30.2	429.0	2.88	770.4	822.1
30		30.0	31.2	459.0	3.08	824.4	879.7
31		31.0	32.2	490.0	3.29	880.3	939.4
	1-1/4	31.8	33.1	522.4	3.51	937.5	1000.2
32		32.0	33.3	523.0	3.51	938.0	1000.9
33		33.0	34.3	556.0	3.74	997.6	1064.5
34		34.0	35.4	590.0	3.96	1058.9	1130.0
	1-3/8	34.9	36.3	625.0	4.20	1121.5	1196.7
35		35.0	36.4	625.0	4.20	1122.1	1197.4
36		36.0	37.4	661.0	4.44	1187.2	1266.8
38		38.0	39.5	737.0	4.95	1322.8	1411.5
	1-1/2	38.1	39.6	736.7	4.95	1322.0	1411.7
40		40.0	41.6	816.0	5.48	1465.7	1564.0

- 交互捻 Regular Lay  1. 35×K7(WA)是最适合用于高起升高度起吊的钢丝绳。  
35×K7(WA) is the most suitable rope for high lifting height application.
- 同向捻 Lang's Lay  2. 35×K7(WA)是阻旋转钢丝绳，并且外层股和内层股均压实。  
35×K7(WA) is a rotation resistant rope, and made with compacted both parts of outer strands and inner strands
- 压实股 Compacted  3. 35×K7(WA)具有相当高的破断拉力，并且对卷筒挤压有很强的抵抗力。  
35×K7(WA) has an extremely high breaking strength with a very strong resistance against drum crushing
- 旋锻 Rotary Swaged  4. 35×K7(WA)钢丝绳有镀锌和光面两种，并且完全被完全润滑。  
The rope is fully lubricated and made out of galvanized/ungalvanized wires
- 塑料填充 PI

www.wzwire.com

