



8×K26(W S)+IWRC

钢丝绳公称直径 Nominal rope diameter		直径误差 Diameter tolerance		钢丝绳近似重量 Approximate unit Wt.		钢丝绳最小破断拉力 Minimum breaking force(Fmin,MBF)	
						公制单位/Metric unit	
		min.	max.			1960 Grade	2160 Grade
mm	inch	mm	mm	kg/100m	lb/ft	kN	kN
20		20.0	20.8	183.0	1.23	351.5	376.1
22		22.0	22.9	222.0	1.49	425.3	455.0
	7/8	22.2	23.1	226.2	1.52	433.4	463.6
24		24.0	25.0	264.0	1.77	506.2	541.5
25		25.0	26.0	287.0	1.93	548.7	587.0
	1	25.4	26.4	296.1	1.99	566.4	606.0
26		26.0	27.0	310.0	2.08	593.4	634.9
27		27.0	28.1	334.0	2.24	640.0	684.7
28		28.0	29.1	359.0	2.41	688.2	736.4
	1-1/8	28.6	29.7	375.0	2.52	718.1	768.4
29		29.0	30.2	386.0	2.59	738.3	789.9
30		30.0	31.2	413.0	2.78	790.1	845.3
31		31.0	32.2	441.0	2.96	843.6	902.6
	1-1/4	31.8	33.1	470.3	3.16	898.4	961.1
32		32.0	33.3	470.0	3.16	898.9	961.8
33		33.0	34.3	499.0	3.35	956.0	1022.8
34		34.0	35.4	530.0	3.56	1014.8	1085.8
	1-3/8	34.9	36.3	561.0	3.77	1074.4	1150.6
35		35.0	36.4	562.0	3.78	1075.4	1150.6
36		36.0	37.4	594.0	3.99	1137.7	1217.2
38		38.0	39.5	662.2	4.45	1267.6	1356.3
	1-1/2	38.1	39.6	662.0	4.45	1268.0	1356.6
40		40.0	41.6	734.0	4.93	1404.6	1502.8
	1-5/8	41.3	43.0	782.8	5.26	1497.6	1602.2
42		42.0	43.7	809.0	5.44	1548.6	1656.8
44		44.0	45.8	888.0	5.97	1699.6	1818.4
	1-3/4	44.5	46.3	907.8	6.10	1738.7	1860.2
45		45.0	46.8	957.0	6.43	1777.7	1901.9
46		46.0	47.8	970.0	6.52	1857.6	1987.4
	1-7/8	47.6	49.5	1034.3	6.95	1981.2	2119.6
48		48.0	49.9	1056.0	7.10	2022.6	2164.0
50		50.0	52.0	1146.0	7.70	2194.7	2348.1
	2	50.8	52.8	1183.1	7.95	2266.0	2424.4
52		52.0	54.0	1240.0	8.33	2373.8	2539.7
54		54.0	56.2	1337.0	8.98	2559.9	2738.8

- 交互捻 Regular Lay 1. 8×K26(W S)+IWRC 压实外层股与绳芯之间具有塑料填充层。
8×K26(W S)+IWRC has a plastic layer between the core and the compacted outer strands
- 同向捻 Lang's Lay 2. 8×K26(W S)+IWRC 具有很高的破断拉力和良好的结构稳定性。
8×K26(W S)+IWRC has a high breakingload and good structural stability
- 压实股 Compacted 3. 8×K26(W S)+IWRC 具有良好的抗挤压性能,适用于多层卷绕。
8×K26(W S)+IWRC has a good resistance against drum crushing and is suitable for multy layer spooling
- 旋锻 Rotary Swaged 4. 8×K26(W S)+IWRC 钢丝绳不能配合使用旋转环。
8×K26(W S)+IWRC must not be used with a swivel
- 塑料填充 PI

www.wzwire.com

