








圆状环形吊索 Round Sling



异型圆状吊索 Eye-eye Round Sling

WLL 极限工作力	SWL, WLL(t), M, CC 安全工作力, 极限工作力, 方式系数, 色码							Double Multi-set SWL (t) 二组合吊索的安全工作力			
	M=1.0	M=0.8	<7	a>7 a<45	a>45 a<60	a<45	a>45 a<60	a<45	a<45	a>45 a<60	a>45 a<60
			M=2.0	M=1.4	M=1.0	M=0.7	M=0.5				
1.0	1.0	0.8	2.0	1.4	1.0	0.7	0.5	1.4	1.1	1.0	0.8
2.0	2.0	1.6	4.0	2.8	2.0	1.4	1.0	2.8	2.2	2.0	1.6
3.0	3.0	2.4	6.0	4.2	3.0	2.1	1.5	4.2	3.4	3.0	2.4
4.0	4.0	3.2	8.0	5.6	4.0	2.8	2.0	5.6	4.5	4.0	3.2
5.0	5.0	4.0	10.0	7.0	5.0	3.5	2.5	7.0	5.6	5.0	4.0
6.0	6.0	4.8	12.0	8.4	6.0	4.2	3.0	8.4	6.7	6.0	4.8
8.0	8.0	6.4	16.0	11.2	8.0	5.6	4.0	11.2	9.0	8.0	6.4
10.0	10.0	8.0	20.0	14.0	10.0	7.0	5.0	14.0	11.2	10.0	8.0
15.0	15.0	12.0	30.0	21.0	15.0	10.5	7.5	21.0	16.8	15.0	12.0
20.0	20.0	16.0	40.0	28.0	20.0	14.0	10.0	28.0	22.4	20.0	16.0
30.0	30.0	24.0	60.0	42.0	30.0	21.0	15.0	42.0	33.6	30.0	24.0
50.0	50.0	40.0	100.0	70.0	50.0	35.0	25.0	70.0	56.0	50.0	40.0
80.0	80.0	64.0	160.0	112.0	80.0	56.0	40.0	112.0	89.6	80.0	64.0
100.0	100.0	80.0	200.0	140.0	100.0	70.0	50.0	140.0	112.0	100.0	80.0

- 1) Flat eye 平吊耳 
- 2) Reversed eye 反向吊耳 
- 3) Folded eye 1/2 width from side 从一边折叠1/2吊耳 
- 4) Folded eye 1/2 width from two side 从两边折叠1/2吊耳 
- 5) Folded eye 1/3 width 折叠1/3吊耳 

安全系数	5:1		6:1		7:1		8:1	
	宽度Width (mm)	最小破断拉力 M.B.L(T)	宽度Width (mm)	最小破断拉力 M.B.L(T)	宽度Width (mm)	最小破断拉力 M.B.L(T)	宽度Width (mm)	最小破断拉力 M.B.L(T)
1	25	5	25/38	6	30	7	50	8
2	50	10	50	12	60	14	76	16
3	75	15	75	18	90	21	100	24
4	100	20	100	24	120	28	125	32
5	100	15	125/150	30	150	35	150	40
6	125/150	20	150	36	180	42	180	48
8	150	40	200	48	240	56	250	64
10	200	50	250	60	300	70	300	80
	特殊要求		ISO 4878		EN 1492:1		AS/NZS	

[www.wzwire.com](http://www.wzwire.com)
