

4VX39S+5FC

4VX48S+5FC

钢丝绳公称直径 Nominal Diameter	钢丝绳近似重量 Approx.Weight	钢丝绳最小破断拉力 (KN) Minimum Breaking Load of Rope (KN)				
		1670MPa	1770MPa	1870MPa	1960MPa	2160MPa
mm	Kg/100m					
8	26.2	38.5	40.8	43.1	45.2	49.8
10	41	60.1	63.7	67.3	70.6	77.8
12	59	86.6	91.8	96.9	102	112
14	80.4	118	125	132	138	152
16	105	154	163	172	181	199
18	133	195	206	218	229	252
20	164	240	255	269	282	311
22	198	291	308	326	342	376
24	236	346	367	388	406	448
26	277	406	431	455	477	526
28	321	471	500	528	553	610
30	369	541	573	606	635	700
32	420	616	652	689	723	796
34	474	695	737	778	816	899
36	531	779	826	872	914	1010
38	592	868	920	972	1020	1120
40	656	962	1020	1080	1130	1240
42	723	1060	1120	1190	1240	1370
44	794	1160	1230	1300	1370	1510
46	868	1270	1350	1420	1490	1650
48	945	1390	1470	1550	1630	1790
50	1030	1500	1590	1680	1760	1940

● 实际重量存在一定误差，误差不大于6%

www.wzwire.com

