



# 8X19S+FC

钢丝绳公称直径(mm)    参考重量 (kg/100m)

最小破断拉力 (kn)

		双强度 (Mpa)				单强度 (Mpa)		
		1180/1770	1320/1620	1370/1770	1570/1770	1570	1620	1770
8	21.8	25.7	26.5	28.1	30.8	29.4	30.4	33.2
9	27.5	32.5	-	35.6	38.9	37.3	-	42
9.5	30.7	36.2	37.3	39.7	43.6	41.5	42.8	46.8
10	34	40.1	41.3	44	48.1	46	47.5	51.9
11	41.1	48.6	50	53.2	58.1	55.7	57.4	62.8
12	49	57.8	59.5	63.3	69.2	66.2	68.4	74.7
12.7	54.8	64.7	66.6	70.9	77.5	74.2	76.6	83.6
13	57.5	67.8	69.8	74.3	81.2	77.7	80.2	87.6
14	66.6	78.7	81	86.1	94.2	90.2	93	102
14.3	69.5	82.1	-	-	98.3	-	-	-
15	76.5	90.3	-	98.9	108	104	-	117
16	87	103	106	113	123	118	122	133
17.5	104	123	-	-	147	-	-	-
18	110	130	134	142	156	149	154	168
19	123	145	149	159	173	166	171	187
20	136	161	165	176	192	184	190	207
20.6	144	170	-	-	204	-	-	-
22	165	194	200	213	233	223	230	251

- 可根据客户的不同要求进行生产
- 可提供高速电梯用钢丝绳

[www.wzwire.com](http://www.wzwire.com)

